

Part Number Coding

CYLINDER LIPS® P106	P106	Travel	Electrical Interface	Calibration Adjusters	Conn / Cable and Length	N	Option 1	Option 2	Option 3	Z code
Internally Mounted Cylinder Sensor										
Travel										
mm of stroke	5-800 mm	Value								
Electrical Interface Options										
Input	Output									
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A								
24V dc nom. +9-28V	0.5-4.5V dc	G								
±15V dc nom. ±9-28V	±5V dc	B								
24V dc nom. +13-28V	0.5 to 9.5V dc	C								
± 15V dc nom. ±13.5-28V	±10 V dc	D								
24V dc nom. +18-28V	4 to 20mA (2 wire)	E								
24V dc nom. +13-28V	4 to 20mA (3 wire sink)	F								
24V dc nom. +13-28V	4 to 20mA (3 wire source)	H								
Calibration Adjusters										
Trim Pots Accessible	Blank									
Sealed Trim Pots	Y									
Connector / Cable										
Connector - Axial IP65	Hirschmann GD series	J								
Connector - Axial IP67	M12 - 4 pin	J +	use Code J plus suffix Z600							
(for sensors with Trim Pots sealed)		Z600								
Connector - Axial IP67	M12 - 4 pin	J +	use Code J plus suffix Z601							
(for sensors with Trim Pots Accessible)		Z601								
Cable - Axial Gland IP67	Please specify cable length in cm.	LXX	eg. L2000 specifies 20 metres of cable with an axial cable gland							
Cable - Axial Short Gland IP67	Please specify cable length in cm.	MXX	Note: restricted cable pull strength							
OPTIONS										
Internal Housing Size		Standard Fit								
20 mm Diameter	Standard Fit	N								
Electronics Housing		Option 1								
Flanged	T									
M18 Thread	P									
Target Tube		Option 2								
Stainless Steel 7.7 mm	Standard Fit	R								
Aluminium 7.0 mm	S									
Flange Style and Position		Option 3								
Please select one.										
None	Please specify flange position xx from Target Tube end in mm. eg. W17.5 specifies a Tempo style flange fitted 17.5 mm from the front face	U								
P&G		Vxx								
Tempo		Wxx								
PH		Xxx								
See Drawing TG24-11 for flange details										

