

Intrinsically Safe - Gas LIPS® SERIES X112			Part Number Coding				
			X112	Travel	A	Blank	Conn / Cable and Length
<b>Gauge Head Linear Sensor</b>							
<b>Travel</b>							
mm of stroke	5-50 mm	Value					
<b>Electrical Interface</b>							
<b>Input</b>	<b>Output</b>						
+ 5 V dc	See below	A					
<b>Adjusts not available</b>							
<b>Connector / Cable</b>							
3 Core Cable - Radial Gland IP67	Please specify cable length in cm.	Ixx	eg. I2000 specifies 20 metres of 3 core cable with a radial cable gland				
5 Core Cable - Radial Gland IP67	Please specify cable length in cm.	IQxx	eg. IQ2000 specifies 20 metres of 5 core cable with a radial cable gland				
Connector - Axial M12		J					
Connector - Radial		K					
3 Core Cable Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland				
5 Core Cable Axial Gland IP67	Please specify cable length in cm.	LQxx	eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland				
<b>Tighter Linearity</b>			<b>Zsuffix</b>				
± 0.1% Linearity	from 10mm stroke only	Z650					

**Please Note: This sensor *must* be used with a Galvanic Isolation Amplifier - See X005 sheet for Output options.**